



# Soleras

Dimensiones				Peso	
Pulg.		mm.		kg./m.	lb./pie
Espesor	Ancho	Espesor	Ancho		
1/8	1/2	3.2	12.7	0.31	0.21
	3/4		19.1	0.47	0.32
	1		25.4	0.63	0.43
	1 1/4		31.7	0.79	0.53
	1 1/2		38.1	0.95	0.64
	2		50.8	1.26	0.85
	2 1/2		63.5	1.58	1.06
5/32	3/4	3.96	19.05	0.59	0.4
3/16	1/2	4.8	12.7	0.47	0.32
	3/4		19.1	0.71	0.48
	1		25.4	0.94	0.64
	1 1/4		31.7	1.18	0.8
	1 1/2		38.1	1.42	0.96
	2		50.8	1.9	1.28
	2 1/2		63.5	2.37	1.59
1/4	1/2	6.3	12.7	0.63	0.43
	3/4		19.1	0.95	0.64
	1		25.4	1.26	0.85
	1 1/4		31.7	1.58	1.06
	1 1/2		38.1	1.9	1.28
	2		50.8	2.53	1.7
	2 1/2		63.5	3.17	2.13
	3		76.2	3.79	2.55
	4		101.6	5.06	3.4
	5		127	6.32	4.25
	6		152.4	7.59	5.1
	8		203.2	10.12	6.8
	10		254	12.65	8.5
12	304.8	15.18	10.2		
5/16	1	7.9	25.4	1.58	1.06
	1 1/4		31.7	1.97	1.33
	1 1/2		38.1	2.37	1.59
	2		50.8	3.16	2.13
	2 1/2		63.5	3.95	2.66
	3		76.2	4.79	3.22
	4		101.6	6.32	4.25
	5		127	7.9	5.31
	6		152.4	9.49	6.38



# Soleras

Dimensiones				Peso	
Pulg.		mm.		kg./m.	lb./pie
Espesor	Ancho	Espesor	Ancho		
3/8	1	9.5	25.4	1.9	1.28
	1 1/4		31.7	2.37	1.59
	1 1/2		38.1	2.84	1.91
	2		50.8	3.79	2.55
	2 1/2		63.5	4.74	3.19
	3		76.2	5.69	3.83
	4		101.6	7.59	5.1
	5		127	9.49	6.38
	6		152.4	11.38	7.65
	8		203.2	15.19	10.21
	10		254	18.99	12.76
	12	304.8	22.78	15.31	
1/2	1 1/2	12.7	38.1	3.81	2.56
	2		50.8	5.06	3.4
	2 1/2		63.5	6.32	4.25
	3		76.2	7.59	5.1
	4		101.6	10.12	6.8
	5		127	12.65	8.5
	6		152.4	15.18	10.2
	8		203.2	20.25	13.61
	10		254	25.31	17.01
			12	304.8	30.39
5/8	4	15.9	101.6	12.65	8.5
	5		127	15.81	10.63
	6		152.4	18.97	12.75
	8		203.2	25.31	17.01
	9		228.6	28.47	19.13
	10		254	31.65	21.27
	12		304.8	37.99	25.53
3/4	2 1/2	19.05	63.5	9.49	6.38
	3		76.2	11.39	7.65
	4		101.6	15.18	10.2
	5		127	18.98	12.75
	6		152.4	22.77	15.3
	8		203.2	30.38	20.41
	9		228.6	34.16	22.96
	10		254	37.98	25.52
			12	304.8	45.57



## Soleras

Dimensiones				Peso	
Pulg.		mm.		kg./m.	lb./pie
Espesor	Ancho	Espesor	Ancho		
1	2	25.4	50.8	10.12	6.80
	3		76.2	15.18	10.20
	4		101.6	20.24	13.60
	5		127	25.31	17.00
	6		152.4	30.37	20.71
	8		203.2	40.49	27.21
	10		254	50.64	34.03
	12		304.8	60.76	40.83
1 1/8	3.15	28.6	80	17.93	12.05
1 1/2	6	38.1	152.4	45.55	20.61

Se manejan en largos de 6.10 m. y algunas medidas en largos de 12.20 m., en grados A-36 y Alta Resistencia.

En caso de requerir alguna medida adicional no incluida en esta tabla, favor de solicitar cotización a su ejecutivo de ventas.